

SPECIFICATIONS

LIGHT DISTRIBUTION III

HOUSING

Heavy wall extruded aluminum, internally sealed for weather proofing. Closed cell neoprene foam gasket is applied between lens frame and housing.

LENS

.125" clear polycarbonate, sealed into mill finish aluminum frame with silicone. Lens frame is hinged and secured with two stainless steel quarter turn fasteners.

REFLECTOR

Specular aluminum, available on type III light distribution.

BALLAST ASSEMBLY

Ballast is high power factor mounted on aluminum tray. The assembly is removable as unit for easy maintenance.

ARM

Mounting arm is supplied with two rods and nuts for easy assembly of luminaire to pole.

FINISH

Polyester powder fuse coating is standard, other finishes available, contact factory.



UL LISTED FOR WET LOCATION


MOUNTING STYLES

DIMENSIONAL DATA

ORDERING INFORMATION




1A - SINGLE ARM



2A - TWIN 90°




2B - TWIN 90°



3A - TRIPLE 90°



3B - TRIPLE 120°



4Q - QUAD

| WATTAGE | A | B | C | EPA |
|------------|-----|----|-----|-----|
| 35 THRU 55 | 30" | 6" | 12" | 1.5 |
| 90 | 34" | 6" | 12" | 1.7 |
| 135 | 44" | 6" | 12" | 2.1 |
| 180 | 58" | 6" | 12" | 2.7 |

- 1 Series
- 2 Mounting Style
- 3 Wattage
- 4 Lamps Type
L - Low Pressure Sodium
- 5 Voltage
120/240, 208/277, 480
- 6 Finish
BZ - Bronze
BK - Black
GN - Green
WT - White
(for any other color consult factory)
- 7 Options
GL - Glass Lens
RCP - Receptacle and Photo Control
PC - Photo Cell Only
FS - Fuse
HS - House Shield

EXAMPLE

SERIES MOUNTING WATTAGE LAMP TYPE VOLTAGE FINISH OPTION
DT - 4Q - 180 - L - 480 - WT - HS